

(19) World Intellectual Property
Organization
International Bureau



533097

(43) International Publication Date
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number
WO 2004/042220 A2

(51) International Patent Classification⁷: **F02M**
(21) International Application Number:
PCT/US2003/034379
(22) International Filing Date: 29 October 2003 (29.10.2003)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
60/422,382 30 October 2002 (30.10.2002) US
(71) Applicant (for all designated States except US): **KINETICO INCORPORATED** [US/US]; 10845 Kinsman Road, Newbury, OH 44065 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and
(75) Inventor/Applicant (for US only): **LILLBACK, Raymond** [US/US]; 1389 Colony Drive, Streetsboro, OH 44241 (US).
(74) Agent: **HLAVKA, John, R.**; Watts Hoffmann Co., L.P.A., P.O. Box 99839, Cleveland, OH 44199-0839 (US).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **BYPASS VALVE**

(57) Abstract: A control valve usable as a bypass/diverter valve for controlling the flow of fluid from a source to a fluid treatment device or other water handling appliance, such as a water softener. The valve has a housing that includes first and second inlet/outlet fittings and first and second fluid transfer fittings and defines a valve chamber in fluid communication with the fittings. A valve member having a valuing portion is rotatably received within the valve chamber. The valuing portion includes a circular base and a disc member spaced above the circular base with a diametral wall extending therebetween which, together define a first fluid flow path through the valve when the valuing portion is in predetermined positions within the valve chamber. The valve chamber includes a wall opening that communicates with a region of the valve chamber above the disc member. The disc member includes an apertured portion for communicating the region of the valve chamber above the disc member with a valuing member region defined between the disc member and a base, such that a second flow path is established by the valuing member region, the disc member apertures, the valve chamber region above the disc member and the wall opening in the valve chamber. The second flow path is isolated from the first flow path. A movement control member in cooperation with a moveable stop pin establishes four different ranges of motion for the valuing member in order to establish four different flow configurations for the control valve.

WO 2004/042220 A2